	CONTACT INFORMATION	ON		
Name:	Pho	ne:		
Address:	Ema	ail:		
Harbor:	Home Zone:	Fishir	ng zone(s):	
Boat Name:	Boat Length:	Horse Power:		
	TRAP INFORMATION			
Trap Type: (wood, wire)	Trap Size: L	W	H	
Total Weight in Trap:	_ Type and Number of Weights in Trap:			
Placement of Weights in Trap:				
EXPER	IMENTAL GROUNDLINE IN	FORMATION		
Groundline type (Neaq sink or DMR Bra	and name)	Diameter of groundli	ne:	
Total Length of Groundline:	# traps on groundline: Dista	ance between traps o	n groundline:	
How are traps attached to groundline?	(gangion, tailors, etc)			
Gangion (or tailor) Type (sink, poly, etc)): Gangion (or tailor) Diamet	ter: Gangion	(or tailor) Length:	
Are gangions attached with knots or spl	lices (please describe):			
Bridle Type (sink, poly, combo):	Diameter of Bridle Rope: _	Leng	th of Bridle:	
Distance from bridle to where the groun	ndline attaches to endline?			
EXPE	ERIMENTAL ENDLINE INFO	DRMATION		
Endline Type (DMR brand or NEAQ We	eak) Diame	eter of Endline:		
Total Length of Endline: C	Composition of Endline: % poly, sink, etc	c (if combined with oth	ner rope):	
Toggles on buoy line (# and size)	Buoy type and	d size:		
How are buoys attached to endline (we	ak link, hogrings, splices, knots)?			

Please draw a diagram of how your gear is set on bottom. Be sure to show how the endline is connected to the groundline, bridle/gangion/tailor configuration (position on trap, length, size, etc), anchors, show location of knots and/or splices in rope, and other information relevant to how your gear is configured. (see sample sheet for further instruction)
Disconding to the state of the
Please draw a diagram of your Surface Buoy system: Be sure to show the buoy configuration starting with the surface buoy,

Please draw a diagram of your Surface Buoy system: Be sure to show the buoy configuration starting with the surface buoy, including toggles, knots, splices, polyball/highflier, attachment of buoy to endline, and the composition of endline (% poly vs sink rope), and other relevant information. (see sample sheet for further instruction)

Do you have any comments or suggestions?

Placement of Pressure Sensors on Lobster Gear

Temperature sensor

All probes must be placed into rubber casings with the spherical end of probe down towards the closed end of casing where twine is attached. The sensors are located on the bottom (flat) end of the probe and should not come into contact with any objects so water can flow freely over sensors. The plastic pin should be secured through the top set of holes.

On Traps: Use a cable tie (zip tie) to secure the sensor (in rubber case)

onto the bottom of the bridle in the center of the trap

On Groundlines: Splice twine into rope up to the edge of the black mark,

leaving the sensor hanging from the rope by a 3" tether

On Gangions: Splice twine into rope (up to the black mark) before the


gangion meets the groundline, leaving the sensor hanging

from the rope by a 3" tether

Record the sensor number on the line corresponding to where it is placed on the gear during the deployment. Record statistical area and site # of deployment.

Complete information on rope type and location on the back side of this page

Pressure Sensor Placement on Triples



Rope Deployment #:

Sensor 1: place in the center of the first trap (at the buoy end) and attach under the bridge

Sensor 2: place in the center of the groundline between first two traps

Sensor 3: place at the end of the gangion before it meets the groundline (for the second trap)

Sensor 4: place in the center of the second trap and attach under the bridge

Sensor 5: place in the center of the groundline between last two traps

Sensor 6: place in the center of the third trap and attach under the bridge

Experimental Groundline Daily Logsheet

Name: _					_	Rope Deploy	ment #:				
Rope Ty	pe (circle on	e): low pr	ofile	sink rope	float rope						
Rope Bra	and / Color):										
Date Hauled	Loca (include symbols points, degrees, l Lat / TD1	such as decimal	Depth (Fathoms)	Bottom Type (ledge, rocky, cobble, gravel, mud, sand, mixed (please define))	Sea State (flat, choppy, rough, other)	Weather (sunny, foggy, drizzle, rain, snow, other)	Wind Direction & Speed (knots)	Orientation of Set (with the tide, across the tide, against the tide, slack)	Set Speed (knots or mph)	Unit of Set Speed (SOG or STW)	Comments

Experimental Rope Gear Handling Assessment

If you fished more than one type of experimental rope, please fill out a separate sheet for each rope type

How was the rope fished?	Number of Hauls
Name:	Place a tick mark each time the rope is hauled. If you have rope deployed on multiple sets of gear, place a
Experimental Rope Type: NEAq sink (light grey), Hyliner lopro (silver/grey with red tracer), Other (please name)	tick mark each time you haul through the gear.
How was gear fished? (pairs, triples, trawls, etc):	
How many sets of gear was the rope fished on?	
Amount of rope fished (total length for all sets in Fathoms)?	
General Location/Area Fished:	
Depth Range Fished (in Fathom):	
Typical Bottom Type Fished:average % of time on bottom types: ledge, rocky, cobble, gravel, mud, sand, mixed (please define	
During Which Months was the Rope Fished:	
Estimated Number of Times Rope was Hauled:	

How did you like the rope?

Please rate the rope on the following characteristics on a scale of 1 to 5 by circling the number that best describes the performance of the rope.

1 (terrible) = hard to imagine a worse rope; 2 (poor) = worse than most ropes I have used in the past; 3 (average) = as good as most ropes I have used in the past; 4 (good) = fishes better than most ropes I have used in the past; 5 (excellent) = hard to imagine a better rope for what I used it for.

Scale: 1 = terrible	2 = poor	3 = average	4 = good	5 = excellent	Comments
Fouling	1	2	3 4	5	
Chafing	1	2	3 4	5	
Hangups	1	2	3 4	5	
Noise	1	2	3 4	5	
Kinking	1	2	3 4	_	
General Durability	1	2	3 4	5	
General Handling	1	2	3 4	_	